



<b>1.Panel spec</b>	
OC supplier(random allocation without appoint)	CHOT/INNOLUX
Size	49.51" diagonal
Backlight	DLED direct Type
Maximum resolution	3840×2160
LCM Center Luminance of White	Min:250cd/m2; Typ:300cd/m2
Contrast ratio (Typ)	5000:1
Response time(Typ)	CHOT Panel :9.5ms
Display scale	16:09
Viewing angle(CR>10)	Typ (H:178° , V:178° )
Display Colors	1.07G
Color Gamut(NTSC)	≥NTSC 62%
<b>2.Hardware Information</b>	
ATV	PAL SECAM
DTV	DVB-T, DVB-T2, DVB-C
CPU Frame	ARM Cortex-A53/1.5GHz/Quad core
GPU	Mali T720MP2/Dual core
RAM(DDR3)	1GB
ROM(Flash)	8GB (16GB optional)
Audio power(Output)	8W+8W
WIFI(Type)	1R1T
HDMI 1.4 (HDCP 1.4)	-
HDMI 2.0 (HDCP 2.2)	3
USB 2.0	2
USB 3.0	-
VGA	-
AV In	1
YPbPr In	-
CI	-
PC Audio	-

RJ-45	1
Earphone	-
Audio In	-
Audio Out	1
Video Out	-
SPDIF Out	1 (coaxial default, optical optional)
<b>3. Software Function</b>	
Channel list	YES
Channel edit	YES
Picture freezing	NO
MTS/NICAM	NICAM
Sleep time setting	YES
Teletext	YES
PVR	YES
EPG	YES
V_CHIP/Parental Guidance	Parental Guidance
CC(Closed caption)	NO
AD(Audio description)	YES
TTS(Text to Speech)	NO
CI+	YES (Optional)
DOLBY	YES (Optional)
HDMI-ARC	HDMI-1
HDMI-CEC	YES
HDMI-MHL	NO
Operation system	Android 6.0
OTA	YES
Hotel mode	COTT HIMS Software
<b>4. Structure Information</b>	
Base model name	BCCE-50 Crescent plastic stand
Size (without stand) L×W×H	1126×70×653mm
Size (with stand) L×W×H	1126×220×711mm
Size (carton) L×W×H	1228×121×740mm
Net Weight (without stand)	9.4kg
Net Weight (with stand)	9.5kg
Gross Weight (without stand)	11.7kg
Gross Weight (with stand)	11.8kg
Size (Wall hanging)	200×200mm
<b>5. Power Management&amp;Safety&amp;Certificate</b>	
Power input	100-240VAc
Fire rating	UL94-HB75

Standby power	≤0.5W
Rated power	130W
Working condition	Temperature:5°C~40°C, Humidity:10%~85%, Atmosphere:86KPa~106KPa
Storage condition	Temperature:-20°C~55°C, Humidity:5%~95%, Atmosphere:86kPa~106kPa

## 6.Accessory

Stand(Optional)	1PCS
Remote control	1PCS
Instruction	1PCS
Warranty card(Optional)	1PCS
Battery(Optional)	2PCS